

Old Faithful in Underground Mine Dewatering

Developed in consultation with the Australia Mining Industry and wholly manufactured by PumpEng for the Underground Mining Industry. Proudly Australian Made.

Parts interchangeable with traditional OEM BIBO ranges. The Raptor® is available 1000V and 415V in 50Hz and 480V and 600V in 60Hz.

Benefits of Raptor® for Mining Operations

PumpEnt



Increase mine performance, productivity and profit by reducing breakdowns and delays.



Reduce workplace hazards by reducing the number of breakdowns.



PumpEng

Reduce equipment lifecycle cost by increasing total pump life.

About Us

PumpEng is on a mission to redefine underground mine dewatering, prioritising excellence at every turn. Our commitment to innovation, reliability, availability, and personalised support throughout the product lifecycle ensures every mine operator a good day at work.

PumpEng is an Australian-based global Original Equipment Manufacturer (OEM) with a rich history of supplying submersible pumps to the mining sector. Renowned for excellence and innovative pumping solutions, we are a trusted global mining partner. Our core competencies include submersible pump design, manufacture, assembly and application guidance. A commitment to eco-friendly solutions reflects environmental responsibility. Our client-centric approach fosters enduring partnerships worldwide, providing exceptional service and support. PumpEng upholds the highest standards and meets international regulations. PumpEng stands as a beacon of global OEM manufacturing, epitomising reliability, innovation, and customer-centricity for the mining sector. We're available, supportive, innovative and consultative.





Power Curves (50 & 60Hz)



Raptor® Specifications

Model	kW (Hp)	Discharge	Voltage (Hz)	Solids Passage in mm	Max Head in m (ft)	Max Flow I/s	Max Diameter mm	Height mm	Weight kg
PE0512291	5 (7)	50mm	415 (50)	8	41 (134)	15	350	550	57
PE0812291	8 (11)	80mm	415 (50)	8	72 (236)	14	380	720	105
PE2012291	20 (27)	100mm	415 (50)	8	74 (243)	39	520	765	185
PE0512391	5 (7)	50mm	1000 (50)	8	41 (134)	15	350	550	57
PE0812391	8 (11)	80mm	1000 (50)	8	72 (236)	14	380	720	105
PE2012391	20 (27)	100mm	1000 (50)	8	74 (243)	39	520	765	185
PE0512491	5 (7)	50mm	600 (60)	8	41 (134)	15	350	550	57
PE0812491	8 (11)	80mm	600 (60)	8	72 (236)	14	380	720	105
PE2012491	20 (27)	100mm	600 (60)	8	74 (243)	39	520	765	185
PE0812591	8 (11)	80mm	480 (60)	8	72 (236)	14	380	720	105
PE2012591	20 (27)	100mm	480 (60)	8	74 (243)	39	520	765	185

Motor Specifications						
Pole	2-Pole					
Insulation Class	Class F/H					
Motor Power Details	1000V, 415V 50Hz 480V, 600V, 1000V 60Hz					
Max Liquid Temp	Fluid at 40°C					
Max Submergence	22m					

Pump Specifications				
Impeller	27 Chrome or CD4			
Wear Parts	Polyurethane Lined			
Mechanical Seal	Sic-Sic			
Bearing	Heavy duty bearings			
Outer Jacket	Aluminium or Stainless Steel			
Shaft	Stainless Steel			





Hire Spare Parts Repairs

Ongoing Support



Tough Submersible Pumps

Explore Your Options

PumpEng Pty Ltd



Perth (08) 9434 9922 U3, 22-24 Alex Wood Drive Forrestdale WA 6112



Townsville (07) 4766 3160 64-66 Crocodile Crescent

Mount St John QLD 4818

Kalgoorlie

(08) 9021 5965



Adelaide

(08) 8448 9830 U3, 9-11 Peekarra Street Regency Park SA 5010

North America +1 (208) 749 7636

635 5th Ave West Twin Falls ID 83301

Email Direct

 \square sales@pumpeng.com.au ()

pumpeng.com.au

International Distribution Network

